



MODEL : SM 10-X5



DESCRIPTION

Very low profile through table Microphone Shock Mount.

- Very low profile through table Microphone Shock Mount.
- Fitted with 5 Pin female XLR input and 5 Pin male XLR output.
- Compatible with all Clockaudio gooseneck microphones.
- Same barrel diameter as Clockaudio C003E-RF, C004E-RF, C011E-RF, C012E-RF, SM20-RF microphones.

Technical	
Dimensions	Height 36mm (1.4”) above table surface. Surface diameter 28mm (1.1”). Body diameter 20mm (0.79”). Body length 63.4mm (2.6”) below surface top (threaded section to securing nut). Total body length 99.5mm (3.9”).
Application	Very low profile through table Microphone Shock Mount.
Type	Through Table Shock Mount
Termination	5 Pin female XLR input and 5 Pin male XLR output
Finish	Top- Satin Black Body - Brass
Architects and engineer specifications	Very low profile through table Microphone Shock Mount. Fitted with 5 Pin female XLR input and 5 Pin male XLR output. Compatible with all Clockaudio gooseneck microphones. Same barrel diameter as Clockaudio C003E-RF, C004E-RF, C011E-RF, C012E-RF, SM20-RF microphones. Height 36mm (1.4”) above table surface. Surface diameter 28mm (1.1”). Body diameter 20mm (0.79”). Body length 63.4mm (2.6”) below surface top (threaded section to securing nut).Total body length 99.5mm (3.9”). Finish: Top - Satin Black / Body – Brass.

